



COBALT SAPPHIRE BBG-2110-H/S • 12G SDI and JPEG-XS* Mini-Converter with HDMI Output



The **SAPPHIRE BBG-2110-H/S** mini-converter addresses the need to display received 12G SDI Baseband or JPEG-XS* content on HDMI monitors in a simple and cost-effective way. The mini-converter is designed to be mounted behind the monitor.

The BBG-2110-H/S is a single channel unit with simultaneous HDMI and 12G SDI outputs.

The converter includes **dual SFP cages** with support for 10G and 25G Ethernet ports, additional 1Gb copper Ethernet port for out of band management, support for SMPTE ST 2022-7 Seamless Switching up to Class C operation for WAN environments, support for NMOS IS-04/IS-05 control and management (both in-band and out-of-band), and in-band PTP support. Available as a passive (**P**), fan-less design for quiet environments. (**A**) Active cooling (fan version) is available.

SAPPHIRE BBG units are capable of fully asynchronous operation and are **IPMX-compliant**.

The SAPPHIRE BBG units are the ideal choice for directly displaying incoming Baseband or JPEG-XS* content on HDMI monitors, including content originating from a WAN connection.

The units can be mounted directly behind the monitor with optional mounting brackets. No need to take up any additional rack space.

Features

Converts 1 JPEG-XS* stream or 12G SDI with associated audio and ancillary data essences to HDMI.	Supports NMOS IS-04/IS-05 control, both in-band and out-of-band.
Supports SMPTE ST 2022-7 Seamless Redundancy up to Class C for WAN operation.	Web interface and DashBoard™ control.
Available with Active cooling fan or Passive fan-less version for quiet operation.	Dual power supply connections for redundancy.
Can be mounted behind the monitor. See mounting bracket options below -	Supports all popular formats: 720p, 1080i, 1080p, 2160p
+JPEG-XS * optional license	Five Year Warranty

COBALT SAPPHIRE BBG-2110-H/S • 12G SDI and JPEG-XS* Mini-Converter with HDMI Output

Ordering Information

BBG-2110-H/S (A or P) frame with redundant power connections and built-in network controller.

(A) Active cooling fan.

(P) Passive cooling - No fan.


+JPEG-XS * License Option

Accessories:

- SAPPHIRE BBG-Desk-top Stand
- SAPPHIRE BBG-Arm Bracket (VESA)
- SAPPHIRE BBG-Wall Bracket
- SAPPHIRE BBG-Monitor Rack Rail Bracket
- PS-40W-761K Second / Redundant power supply

SAPPHIRE BBG-2110-H/S


Single channel converter from IP or 12G SDI to HDMI



COBALT SAPPHIRE BBG-2110-H/S • 12G SDI and JPEG-XS* Mini-Converter with HDMI Output




BBG-2110-2H & H/S
OVERALL DIMENSIONS




(NOT TO SCALE)

THIS UNIT HAS PASSIVE COOLING (no fan)
Dimensions: 8" w x 5.5" d x 2.5" h



THIS UNIT HAS AN ACTIVE COOLING (FAN)
DIMENSIONS: 4" w x 5.5" d x 1.5" h



COBALT SAPPHIRE BBG-2110-H/S • 12G SDI and JPEG-XS* Mini-Converter with HDMI Output



Options and Accessories:

- SAPPHIRE BBG-Stand
- SAPPHIRE BBG-Arm Bracket (VESA)
- SAPPHIRE BBG-Wall Bracket
- SAPPHIRE BBG-Monitor Rack Rail Bracket
- Spare / Redundant power supply PS-40W-761K