


9490-OS • Fiber Optic Passive Splitters for 20-Slot Frames



The **9490-0S** series of passive splitters offer a flexible, cost-effective solution of fiber distribution using our HPF-9000 or OG3-FR 20-slot frames. Similar to a DA, these splitters provide branching of optical signals. Fully passive with low-loss optics, the devices require no frame power or communications for operation.

The 9490-OS models are available in 1x2, 1x4, and 1x8 splitting fan-outs. Fully passive operation helps ensure the utmost in reliability. Each device occupies 2 frame slots.

9490-OS Models

- 94900S-1X2-LC Optical 1x2 Splitter (LC connectors)
- 94900S-D1X2-LC Dual Optical 1x2 Splitter (LC connectors)
- 94900S-1X4-LC Optical 1x4 Splitter (LC connectors)
- 94900S-D1X4-LC Dual Optical 1x4 Splitter (LC connectors)
- 94900S-1X8-LC Optical 1x8 Splitter (LC connectors)

FEATURES

Modular, scalable design allows easy expansion. Available in several 1x2, 1x4, and 1x8 versions.

Fully passive design using low-loss filters. Requires no frame power or communications.

Wavelength agnostic operation - supports 1270nm thru 1620nm signals

Supports single-mode fiber

Fits 20-slot openGear frames using blindmate-connection rear I/O modules

Five year warranty

Rear Module I/O Connections 9490OS-D1X2-LC 9490OS-1X4-LC 9490OS-D1X4-LC 9490OS-1X2 LC 9490OS-1X8-LC Fiber In Fiber In B Not Used Not Used Not Used Fiber In B Fiber Out A1 Fiber Out B1 Fiber Out Fiber Out 2 Fiber Out ₹0 Fiber Out B2 Fiber Out 3 Fiber Out 4 Fiber Out 2 Fiber Out A2 Fiber Out 2 €0 Fiber Out A2 \mathbb{C} Co. o", Fiber Out A3 Ç0 Fiber Out 5 o Fiber Out 3 Not Used Fiber Out B2 Fiber Out 4 Fiber Out A4 ,0 Fiber Out B4 Fiber Out 7 <u>ڙ</u>و Fiber Out 8

SPECIFICATIONS

Wavelength Range

1260nm to 1650nm

Return Loss (minimum)

50 dB

Insertion Loss (maximum)

94900S-1x2, 94900S-D1x2: 4 dB 94900S-1x4, 94900S-D1x4: 8 dB

94900S-1x8: 11 dB

Uniformity

94900S-1x2, 94900S-D1x2: 0.4 dB 94900S-1x4, 94900S-D1x4: 0.6 dB 94900S-1x8: 0.8 dB

Directivity

55 dB

Slots required per device

2

Connector Type

Single Mode, LC/UPC

ORDERING INFORMATION

94900S-1x2-LC Optical 1x2 Splitter (LC connectors only). Includes type LC connector Rear I/O Module

94900S-D1x2-LC Dual Optical 1x2 Splitter (LC connectors only). Includes type LC connector Rear I/O Module

 $\bf 94900S\text{-}1x4\text{-}LC$ Optical 1x4 Splitter (LC connectors only). Includes type LC connector Rear I/O Module

94900S-D1x4-LC Dual Optical 1x4 Splitter (LC connectors only). Includes type LC connector Rear I/O Module

 $\bf 94900S\text{-}1x8\text{-}LC$ Optical 1x8 Splitter (LC connectors only). Includes type LC connector Rear I/O Module

